

# SPECIFICATIONS

## 8000 series

### Pocket-size Mobile Computer



|  |   | 8000   | 8001                                     | 8061                                     | 8071             |
|--|---|--|--|--|------------------|
| <b>Wireless Communication</b>                        | Options   | Batch  |  | Bluetooth                                | Wi-Fi            |
|  | Specifications  | Infrared   |  | BT Class 1                               | 802.11b/g        |
|  | Coverage line of sight  | Typically 30 cm / 12 in.   |  | 250 m / 820 ft.                          | 350 m / 1148 ft. |
| <b>Power</b>   | Operation battery   | 2 AAA alkaline   | Li-ion 3.7 V 700 mAh                     |  |                  |
|  | Backup battery  | Rechargeable lithium 3.0 V, 7.0 mAh  |  |  |                  |
|  | Working time<br><i>laser, one scan per five seconds</i>   | 100 hours  |  | 36 hours                                 | 22 hours         |
|  | Data retention  | 30 days  |  |  |                  |
| <b>General Characteristics</b>                       | CPU   | 16-bit CMOS, low power consumption   |  |  |                  |
|  | Program memory  | 2MB flash memory   |  |  |                  |
|  | Data memory   | 2MB SRAM   |  |  |                  |
|  | Display   | LCD 100 x 64 with LED backlight  |  |  |                  |
|  | Keypad  | 21 rubber keys with LED backlight  |  |  |                  |
|  | Buzzer  | Programmable, 1 KHz to 4 KHz   |  |  |                  |
|  | LED   | Dual color: red and green  |  |  |                  |
| <b>Dimensions</b>                                    | Size L x W x H  | 122 x 56 x 23 mm<br>4.8 x 2.2 x 0.9 in.  | 122 x 56 x 32 mm<br>4.8 x 2.2 x 1.25 in. | 143 x 57 x 35 mm<br>5.6 x 2.25 x 1.4 in. |                  |
|  | Weight<br><i>laser including battery</i>  | 123 g / 4.4 oz.  | 120 g / 4.2 oz.                          | 125 g / 4.4 oz.                          | 166 g / 5.9 oz.  |
| <b>Scanner</b>                                       | Light source  | Linear imager: 650 nm red LED / Laser: visible laser diode   |  |  |                  |
|  | Scan rate   | Linear imager/Laser: 100 scans per second  |  |  |                  |
|  | Scan angle  | Laser: 47°   |  |  |                  |
|  | Reading range   | Linear imager: 3 to 29 cm / 1.2 to 11.4 in.<br>Laser: 1 to 45 cm / 0.4 to 1.5 ft. <i>dependent on barcode resolution</i> |  |  |                  |
| <b>Environmental</b>                                 | Operating temperature   | -10°C to 60°C / 14°F to 140°F  |  |  |                  |
|  | Storage temperature   | -20°C to 70°C / -4°F to 158°F  |  |  |                  |
|  | Humidity  | Operating: non-condensed 10% to 90% / Storage: 5% to 95%   |  |  |                  |
|  | Impact resistance   | 1.2 meter / 4 ft. drops onto concrete, 5 drops per 6 sides   |  |  |                  |
|  | Electrostatic discharge   | ± 15 kV air discharge, ± 8 kV direct discharge   |  |  |                  |
| EMC regulation                                       | FCC, CE, and C-Tick approved  |  |  | FCC, CE, C-Tick, DGT, BSMI, TELEC, MIC   |                  |
| <b>Programming</b>                                   | C, Basic, and Windows-based applications generator  |  |  |  |                  |
| <b>Accessories</b>                                   | Charging & communication cradle (serial & USB), Modem cradle (56K), Ethernet cradle (10/100 BaseT), Battery gang charger      |  |  |  |                  |
| <b>Acoustic Coupler</b><br>8020/8021 available in US | Data rate/format: 1200, O/E/N, 7/8, 1/2 stop bits<br>Sound frequency: 1.2 KHz ± 5%, 2.2 KHz ± 5% Modulation type: Bell202/FSK |  |  |  |                  |
| <b>Warranty</b>                                      | 1 year  |  |  |  |                  |

## ACCESSORIES



Communication Cradle



Charging and Communication Cradle



56 Kbps Modem  
10/100 Mbps Ethernet Cradle



4-slot Battery Charger



© 2006 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All trademarks and trade names are those of their respective owners.



**HEADQUARTERS**  
CipherLab Co., Ltd.  
12F, 333 Dunhua S. Rd., Sec. 2  
Taipei, Taiwan 106  
Tel +886 2 8647 1166  
Fax +886 2 8732 2255  
www.cipherlab.com

**CipherLab China**  
Suite 1306, 1065A, Jaojiabang Rd.  
Xuhui District, Shanghai,  
China 200031  
Tel +86 21 3368 0288  
Fax +86 21 3368 0286

**CipherLab USA**  
2552 Summit Avenue  
Plano, Texas USA 75074  
Tel +1 469 241 97799  
Toll Free 888 300 9779  
Fax +1 469 241 0697

**CipherLab EMEA**  
Airedale House  
Clayton Wood Rise  
Leeds, LS16 6RF, UK  
Tel +44 113 274 7823  
Fax +44 113 274 7822