



Light Source	650 nm
Scan Rate	72 scan/sec
Sensor	Laser Diode
Resolution	4 mil
Print Contrast Ratio	35%
Distance	0-64 mm
Skew/Pitch Angle	Skew $\pm 52^\circ$ , Pitch $\pm 68^\circ$
D.O.F	64 mm
Impact Tolerance	1.5 M
Interface/ Profile	USB , KWB , RS232
Symbologies	1D : UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Codabar, Interleaved 2 of 5, Code 128 , Code 93 , MSI Plessey , Code 11 , Airline 2 of 5 (15 digits) ,Matrix 2 of 5 , Telepen , UK Plessey , TRI-OPTIC , Standard 2 of 5, Airline (13 digits)
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 60°C
Relative Humidity	5%-95% non-condensing
Dimension	L 110 mm x W 70 mm x H 153 mm
Weight	120g
Safety Approval	FCC , CE , BSMI (Ready in July)



### Unitech America

Los Angeles, Houston  
<http://us.ute.com> e-mail: [info@us.ute.com](mailto:info@us.ute.com)  
<http://can.ute.com> [info@can.ute.com](mailto:info@can.ute.com)  
 Mexico  
<http://latin.ute.com> e-mail: [info@latin.ute.com](mailto:info@latin.ute.com)

### Unitech Asia Pacific & Middle East

Taipei  
<http://apac.ute.com> [info@apac.ute.com](mailto:info@apac.ute.com) / [info@india.ute.com](mailto:info@india.ute.com)  
<http://mideast.ute.com> [info@mideast.ute.com](mailto:info@mideast.ute.com)

### Unitech Japan

Tokyo  
<http://jp.ute.com> e-mail: [info@jp.ute.com](mailto:info@jp.ute.com)

### Unitech Europe

Tilburg / Netherlands  
<http://eu.ute.com> e-mail: [info@eu.ute.com](mailto:info@eu.ute.com)

### Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen  
<http://cn.ute.com> [info@cn.ute.com](mailto:info@cn.ute.com)  
 Taipei <http://tw.ute.com> [info@tw.ute.com](mailto:info@tw.ute.com)

### Head Office

Taipei  
<http://www.ute.com> e-mail: [info@hq.ute.com](mailto:info@hq.ute.com)